

## Specification Sheet

Part Number: 151-01246



Head design contains clamping rails to provide full circumferential compression around bundles. Bent tail allows for quick insertion into head.

Conn. Clip w/Oval Fir Tree, 0.51-6.75mm Panel Thick, 6.2-13.0mm Hole, PA66HIRHSUV, Black, 5000/ctn

**Article Number** 151-01246

**Type** CCOVAL4

**Color** Black (BK)

**Quantity Per** carton

**Product Description** Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

**Short Description** Conn. Clip w/Oval Fir Tree, 0.51-6.75mm Panel Thick, 6.2-13.0mm Hole, PA66HIRHSUV, Black, 5000/ctn

**Global Part Name**

CCOVAL4-PA66HIRHSUV-BK

**Length L (Imperial)**

0.93

**Length L (Metric)**

23.60

**Fixation Method**

Fir Tree for oval holes

**Width W (Imperial)**

0.69

**Width W (Metric)**

17.53

**Height H (Imperial)**

0.85

**Height H (Metric)**

21.6

**Panel Thickness Min (Imperial)**

0.023

**Panel Thickness Max (Imperial)**

0.27

**Panel Thickness Min (Metric)**

0.6

**Panel Thickness Max (Metric)**

6.75

**Mounting Hole Diameter D (Imperial)**

0.24 x 0.48 " 0.26 x 0.50 " 0.26 x 0.51 " 0.28 x 0.47

**Mounting Hole Diameter D (Metric)**

6.2 x 12.2 mm 6.5 x 13.0 mm 6.5 x 12.5 mm 7.0 x 12.0 mm

**Mounting Hole Diameter D Min (Imperial)**

0.24

**Mounting Hole Diameter D Max (Imperial)**

0.51

**Mounting Hole Diameter D Max (Metric)** 13.0

**Material** Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

**Material Shortcut** PA66HIRHSUV

**Operating Temperature** -40°F to +221°F (-40°C to +105°C)

**Reach Compliant (Article 33)** Yes

**ROHS Compliant** Yes

**Package Quantity (Imperial)** 5000

**Package Quantity (Metric)** 5000

**Customs Number** 3926909988