

Specification Sheet

Part Number: 151-01254

Design helps silence and stabilize.

Arrowhead-style mount provides low insertion and high extraction force.

Anti-rotational oval fastener forces bundle to travel in intended direction.

Product Image

Seal restricts water and debris from passing through mounting hole.

Connector Clip, Hole Dia. 6.2 x 12.2mm, Panel Thickness 0.60 - 2.0mm, PA66HIRHS/EPDM, Black, 5000/pkg

Article Number

151-01254

Type

TCCSFT6.2x12.2-MD

Color

Black (BK)

Quantity Per

bag

Product Description

Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description

Connector Clip, Hole Dia. 6.2 x 12.2mm, Panel Thickness 0.60 - 2.0mm, PA66HIRHS/EPDM, Black, 5000/pkg

Global Part Name

TCCSFT6.2x12.2-MD-PA66HIRHS/EPDM-BK

Length L (Metric)	22.0
Width W (Metric)	19.0
Height H (Metric)	15.0
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.08
Panel Thickness Min (Metric)	0.60
Panel Thickness Max (Metric)	2.0
Mounting Hole Diameter D (Imperial)	0.24 " x 0.48
Mounting Hole Diameter D (Metric)	6.2 x 12.2 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.48
Mounting Hole Diameter D Max (Metric)	12.2
Disc Diameter (Imperial)	0.63 " x 0.87
Material	Ethylene Propylene Diene Terpolymer rubber free of Nitrosamine (EPDM) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS EPDM

Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)