

Specification Sheet

Part Number: 151-01259



Head design contains clamping rails to provide full circumferential compression around bundles. Bent tail allows for quick insertion into head.

Conn. Clip w/Oval Fir Tree, 0.51-6.0mm Panel Thick, 6.2-13.0mm Hole, PA66HIRHS, Natural, 5000/ctn

Article Number 151-01259

Type CCOVAL

Color Natural (NA)

Quantity Per carton

Product Description Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description Conn. Clip w/Oval Fir Tree, 0.51-6.0mm Panel Thick, 6.2-13.0mm Hole, PA66HIRHS, Natural, 5000/ctn

Global Part Name

CCOVAL-PA66HIRHS-NA

Length L (Imperial)

1.16

Length L (Metric)

29.34

Fixation Method

Fir Tree for oval holes

Width W (Imperial)

0.69

Width W (Metric)

17.53

Height H (Imperial)

0.79

Height H (Metric)

19.98

Panel Thickness Min (Imperial)

0.023

Panel Thickness Max (Imperial)

0.24

Panel Thickness Min (Metric)

0.6

Panel Thickness Max (Metric)

6.0

Mounting Hole Diameter D (Imperial)

0.24 x 0.48 " 0.26 x 0.50 " 0.26 x 0.51 " 0.28 x 0.47

Mounting Hole Diameter D (Metric)

6.5 x 12.5 mm 6.5 x 13.0 mm 7.0 x 12.0 mm 6.2 x 12.2 mm

Mounting Hole Diameter D Min (Imperial)

0.24

Mounting Hole Diameter D Max (Imperial)

0.51

Mounting Hole Diameter D Max (Metric) 13.0

Material Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut PA66HIRHS

Operating Temperature -40°F to +230°F (-40°C to +110°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 5000

Package Quantity (Metric) 5000

Customs Number 3926909988