

Specification Sheet

Part Number: 151-01286

HellermannTyton Connector Clips provide a single method to mount connectors to various surfaces in a variety of applications.

Highly engineered designs feature anti-rattle discs, anti-rotation oval fir trees and clamps for mounting on edges.



An assortment of Connector Clips is available to fit the variety of connector slot designs made by most of the largest global connector manufacturers.

Connector Clip with Oval Fir Tree, 0.51-6.75mm Panel Thick., 6.2-13.0mm Hole, PA66HIRHSUV, Black, 4000/ctn

Article Number 151-01286

Type CCOVAL5

Color Black (BK)

Quantity Per carton

Product Description Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description Connector Clip with Oval Fir Tree, 0.51-6.75mm Panel Thick., 6.2-13.0mm Hole, PA66HIRHSUV, Black, 4000/ctn

Global Part Name

CCOVAL5-PA66HIRHSUV-BK

Length L (Imperial)

0.93

Length L (Metric)

23.60

Fixation Method

Fir Tree for oval holes

Width W (Imperial)

0.69

Width W (Metric)

17.6

Height H (Imperial)

0.77

Height H (Metric)

19.55

Panel Thickness Min (Imperial)

0.02

Panel Thickness Max (Imperial)

0.27

Panel Thickness Min (Metric)

0.5

Panel Thickness Max (Metric)

6.75

Mounting Hole Diameter D (Imperial)

0.24 x 0.48 " 0.26 x 0.50 " 0.26 x 0.51 " 0.28 x 0.47

Mounting Hole Diameter D (Metric)

6.2 x 12.2 mm 6.5 x 12.5 mm 7.0 x 12.0 mm 6.5 x 13.0 mm

Mounting Hole Diameter D Min (Imperial)

0.24

Mounting Hole Diameter D Max (Imperial)

0.24

Mounting Hole Diameter D Max (Metric) 6.2

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

UV Resistant (Yes/No) Yes

Use Conditions For Indoor and Outdoor Use

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) No

Package Quantity (Imperial) 4000

Package Quantity (Metric) 4000

Customs Number 3926909988