

Specification Sheet

Part Number: 151-01286



Connector Clip w/Oval Fir Tree, 0.51 - 6.75 mm Panel Thickness, Hole Dia. 6.2–13.0mm, PA66HIRHS, Black, 4000/ctn

Article Number	151-01286
Type	CCOVAL5
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• Head design contains clamping rails to provide full circumferential compression around bundles.• Bent tail allows for quick insertion into head.
Quantity Per	carton

Product Description

Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description	Connector Clip w/Oval Fir Tree, 0.51 - 6.75 mm Panel Thickness, Hole Dia. 6.2–13.0mm, PA66HIRHS, Black, 4000/ctn
Global Part Name	CCOVAL5-PA66HIRHS-BK
Length L (Imperial)	0.93
Length L (Metric)	23.60
Fixation Method	Fir Tree for oval holes
Width W (Imperial)	0.69
Width W (Metric)	17.53
Height H (Imperial)	0.77
Height H (Metric)	19.55
Panel Thickness Min(Imperial)	0.02
Panel Thickness Max(Imperial)	0.27
Panel Thickness Min (Metric)	0.51
Panel Thickness Max (Metric)	6.75
Mounting Hole Diameter D (Imperial)	0.24 x 0.48 " 0.26 x 0.50 " 0.26 x 0.51 " 0.28 x 0.47
Mounting Hole Diameter D (Metric)	6.5 x 13.0 mm 7.0 x 12.0 mm 6.5 x 12.5 mm 6.2 x 12.2 mm
Mounting Hole Diameter D Min (Imperial)	0.24

Mounting Hole Diameter D Max (Imperial)

0.51

Mounting Hole Diameter D Max (Metric)

13.0

Material

Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut

PA66HIRHS

Operating Temperature (Metric)

-40°F to +230°F (-40°C to +110°C)

Package Quantity(Imperial)

4000

Package Quantity (Metric)

4000

Customs Number

3926909988