

Specification Sheet

Part Number: 151-01286



Connector Clip w/Oval Fir Tree, 0.51 - 6.75 mm Panel Thickness, Hole Dia. 6.2–13.0mm, PA66HIRHSUV, Black, 4000/ctn

Article Number	151-01286
Type	CCOVAL5
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• Head design contains clamping rails to provide full circumferential compression around bundles.• Bent tail allows for quick insertion into head.
Quantity Per	carton

Product Description Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description Connector Clip w/Oval Fir Tree, 0.51 - 6.75 mm Panel Thickness, Hole Dia. 6.2–13.0mm, PA66HIRHSUV, Black, 4000/ctn

Global Part Name CCOVAL5-PA66HIRHSUV-BK

Length L (Imperial) 0.93

Length L (Metric) 23.60

Fixation Method Fir Tree for oval holes

Width W (Imperial) 0.69

Width W (Metric) 17.53

Height H (Imperial) 0.77

Height H (Metric) 19.55

Panel Thickness Min(Imperial) 0.02

Panel Thickness Max(Imperial) 0.27

Panel Thickness Min (Metric) 0.51

Panel Thickness Max (Metric) 6.75

Mounting Hole Diameter D (Imperial)	0.24 x 0.48 " 0.26 x 0.50 " 0.26 x 0.51 " 0.28 x 0.47
Mounting Hole Diameter D (Metric)	6.5 x 12.5 mm 6.2 x 12.2 mm 7.0 x 12.0 mm 6.5 x 13.0 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.51
Mounting Hole Diameter D Max (Metric)	13.0

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Operating Temperature (Metric) -40°F to +221°F (-40°C to +105°C)

Package Quantity(Imperial) 4000

Package Quantity (Metric) 4000

Customs Number 3926909988

Content Unit(BMEcat) pcs.

