

Specification Sheet

Part Number: 151-01296

HellermannTyton connector clips provide a simple and easy method for mounting connectors to a mounting surface in a variety of applications. Detailed designs include anti-rattle disc features, anti-rotation oval fir trees, and clamps for mounting on edges.



HellermannTyton offers an assortment of connector clips that are available for a variety of connector slot designs found on most of the largest global connector manufacturers.

Connector Clip, 9.0–17.0mm Hole Dia., PA66HIRHSUV, Black, 3000/carton

Article Number 151-01296

Type CC18

Color Black (BK)

Quantity Per carton

Product Description Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description	Connector Clip, 9.0–17.0mm Hole Dia., PA66HIRHSUV, Black, 3000/carton
Global Part Name	CC18-PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	35
Minimum Tensile Strength (Metric)	155
Length L (Imperial)	1.19
Length L (Metric)	30.29
Fixation Method	Fir Tree
Width W (Imperial)	0.80
Width W (Metric)	20.32
Height H (Imperial)	0.93
Height H (Metric)	23.57
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.37
Panel Thickness Min (Metric)	0.51
Panel Thickness Max (Metric)	9.5

Mounting Hole Diameter D (Imperial)	0.35 x 0.67
Mounting Hole Diameter D (Metric)	9.0 x 17.0 mm
Mounting Hole Diameter D Min (Imperial)	0.35
Mounting Hole Diameter D Max (Imperial)	0.67
Mounting Hole Diameter D Max (Metric)	17.0

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) No

Package Quantity (Imperial) 3000

Package Quantity (Metric) 3000

Customs Number 3926909988

