

Specification Sheet

Part Number: 151-01297



Connector Clip, Mounting Hole Dia. 8.0–15.0mm, PA66HIRHS, Black, 5000/carton

Article Number	151-01297
Type	CC16
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• HellermannTyton connector clips provide a simple and easy method for mounting connectors to a mounting surface in a variety of applications.• Detailed designs include anti-rattle disc features, anti-rotation oval fir trees, and clamps for mounting on edges.• HellermannTyton offers an assortment of connector clips that are available for a variety of connector slot designs found on most of the largest global connector manufacturers.
Quantity Per	carton

Product Description

Connector Clips are designed with various fixing point designs, to accommodate the many connectors out in the market. This specific connector clip is designed for a commonly used automotive connector. The width and the height of the fixation point creates minimal rattle when secured. The innovative design of the fir tree creates an interface with four different size holes that are common in the automotive industry. The fir tree branch design on all four sides makes a 360-degree interface with the panel, creating a more secure fit into the hole.

Short Description

Connector Clip, Mounting Hole Dia. 8.0–15.0mm, PA66HIRHS, Black, 5000/carton

Global Part Name

CC16-PA66HIRHS-BK

Minimum Tensile Strength (Imperial)

25

Minimum Tensile Strength (Metric)

110

Length L (Imperial)

1.18

Length L (Metric)

30.0

Fixation Method

Fir Tree

Width W (Imperial)

0.72

Width W (Metric)

18.2

Height H (Imperial)

0.92

Height H (Metric)

23.4

Panel Thickness Min(Imperial)

0.02

Panel Thickness Max(Imperial)

0.31

Panel Thickness Min (Metric) 0.60

Panel Thickness Max (Metric) 7.75

Mounting Hole Diameter D (Imperial) 0.31 " x 0.55 " 0.31 " x 0.59

Mounting Hole Diameter D (Metric) 8.0 x 14.0 mm 8.0 x 15.0 mm

Mounting Hole Diameter D Min (Imperial) 0.31

Mounting Hole Diameter D Max (Imperial) 0.59

Mounting Hole Diameter D Max (Metric) 15.0

Material Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut PA66HIRHS

Operating Temperature (Metric) -40°F to +230°F (-40°C to +110°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Package Quantity(Imperial) 5000

Package Quantity (Metric) 5000

Customs Number 3926909987

