

## Specification Sheet

Part Number: 151-01304



Easy assembly without the need of a tool.  
Disc covers mounting hole and minimizes ingress of dust, dirt and water.

Push Pin, Mounting Hole Dia. M6, PA66HIRHSUV, Black, 5000/carton

<b>Article Number</b>	151-01304
<b>Type</b>	M6PUSHPIN
<b>Color</b>	Black (BK)
<b>Quantity Per</b>	carton
<b>Product Description</b>	Developed especially for the automotive industry in applications including trunks, doors, wheel housings and dash panels.
<b>Short Description</b>	Push Pin, Mounting Hole Dia. M6, PA66HIRHSUV, Black, 5000/carton
<b>Global Part Name</b>	M6PUSHPIN-PA66HIRHSUV-BK

<b>Minimum Tensile Strength (Imperial)</b>	25
<b>Minimum Tensile Strength (Metric)</b>	110
<b>Length L (Imperial)</b>	0.51
<b>Length L (Metric)</b>	12.50
<b>Fixation Method</b>	Fir Tree
<b>Width W (Imperial)</b>	0.49
<b>Width W (Metric)</b>	12.5
<b>Height H (Imperial)</b>	0.53
<b>Height H (Metric)</b>	13.36
<b>Panel Thickness Min (Imperial)</b>	0.59
<b>Panel Thickness Max (Imperial)</b>	0.59
<b>Panel Thickness Min (Metric)</b>	15.0
<b>Panel Thickness Max (Metric)</b>	15.0
<b>Mounting Hole Diameter D (Imperial)</b>	0.24
<b>Mounting Hole Diameter D (Metric)</b>	M6
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.24
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.24

**Stud Diameter (Metric)**

M6

**Material**

Polyamide 6.6 high impact modified, heat and UV stabilized  
(PA66HIRHSUV)

**Material Shortcut**

PA66HIRHSUV

**Flammability**

UL 94 HB

**Halogen Free**

Yes

**Operating Temperature**

-40°F to +221°F (-40°C to +105°C)

**Package Quantity (Imperial)**

5000

**Package Quantity (Metric)**

5000

**Customs Number**

3926909988