

## Specification Sheet

Part Number: 151-01311



Bundling clip allows bundle to be parallel, perpendicular or offset from the panel and mounting hole for routing versatility.

Compact I-beam design provides a robust solution for all bundles, small to large.

Used in conjunction with HellermannTyton's 4x oval push pins, bundling clip prevents rotation of the bundle.

Oval hole can also be used as a portable hole joining two routings together.

Bundling Clip, 90 Deg with 6.5x12.5 Oval Hole, 40mm Long, PA66HIRHSUV, Black, 4000/ctn

|                            |   |
|----------------------------|---|
| <b>Article Number</b>      | 151-01311   |
| <b>Type</b>                | TC90OVAL  |
| <b>Color</b>               | Black (BK)  |
| <b>Quantity Per</b>        | carton  |
| <b>Product Description</b> | HellermannTyton's bundling clips allow a harness to be routed around a corner and attached to the panel at this location. |
| <b>Short Description</b>   | Bundling Clip, 90 Deg with 6.5x12.5 Oval Hole, 40mm Long, PA66HIRHSUV, Black, 4000/ctn                                    |

**Global Part Name** TC90OVAL-PA66HIRHSUV-BK

**Length L (Imperial)** 1.47

**Length L (Metric)** 37.3

**Fixation Method** Bolt

**Width W (Imperial)** 0.59

**Width W (Metric)** 15.0

**Height H (Imperial)** 1.66

**Height H (Metric)** 40.8

**Mounting Hole Diameter D (Imperial)** 0.27 x 0.51

**Mounting Hole Diameter D (Metric)** 6.5 x 12.5 mm

**Mounting Hole Diameter D Min (Imperial)** 0.27

**Mounting Hole Diameter D Max (Imperial)** 0.51

**Mounting Hole Diameter D Max (Metric)** 12.5

**Material** Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

|                                     |                                   |
|-------------------------------------|-----------------------------------|
| <b>Material Shortcut</b>            | PA66HIRHSUV                       |
| <b>Flammability</b>                 | UL 94 HB                          |
| <b>Halogen Free</b>                 | Yes                               |
| <b>Operating Temperature</b>        | -40°F to +221°F (-40°C to +105°C) |
| <b>Reach Compliant (Article 33)</b> | Yes                               |
| <b>ROHS Compliant</b>               | Yes                               |
| <b>Package Quantity (Imperial)</b>  | 4000                              |
| <b>Package Quantity (Metric)</b>    | 4000                              |
| <b>Customs Number</b>               | 3926909988                        |