

Specification Sheet

Part Number: 151-01317



Low insertion force enables fast, tool-less mounting.
High extraction resistance means clamp and mount stay put.
Top disc covers mounting hole and minimizes ingress of dust, dirt and water.

Push Pin, Mounting Hole Dia. 6.5mm, PA66HIRHSUV, Black, 5000/carton

Article Number 151-01317

Type FT6.5 Plug

Color Black (BK)

Quantity Per carton

Product Description The Push Pin is a convenient fir tree fastener used to secure the Ratchet P-Clamp with metal base plate to a surface with a 6.5 mm hole.

Short Description Push Pin, Mounting Hole Dia. 6.5mm, PA66HIRHSUV, Black, 5000/carton

Global Part Name FT6.5 Plug-PA66HIRHS-BK

Minimum Tensile Strength (Imperial)	25
Minimum Tensile Strength (Metric)	110
Length L (Imperial)	0.76
Length L (Metric)	18.60
Fixation Method	Fir Tree
Width W (Imperial)	0.62
Width W (Metric)	15.7
Height H (Imperial)	0.48
Height H (Metric)	12.5
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.24
Panel Thickness Min (Metric)	0.60
Panel Thickness Max (Metric)	6.0
Mounting Hole Diameter D (Imperial)	0.24 - 0.27
Mounting Hole Diameter D (Metric)	6.1 - 6.9 mm
Mounting Hole Diameter D Min (Imperial)	0.24

Mounting Hole Diameter D Max (Imperial) 0.27

Mounting Hole Diameter D Max (Metric) 6.9

Disc Diameter (Metric) 18.6

Disc Diameter (Imperial) 0.73

Material Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut PA66HIRHS

Flammability UL 94 HB

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Package Quantity (Imperial) 5000

Package Quantity (Metric) 5000

Customs Number 3926909988