

Specification Sheet

Part Number: 151-01397



Connector Clip, Mounting Hole Dia. 9.0–17.0mm, PA66HIRHS, Black, 2000/carton

Article Number	151-01397
Type	CC20
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• Connector clip design to meet USCAR EWCAP-005-7 clip slot specifications, assuring compliance.• Meets installation and extration requirements of SAE/USCAR-2, delivering easy insertion with reliable performance.• Long fir tree designed for use in thicker panels up to 9.5 mm.• Oval fir tree prevents rotation in 9x17 mm holes.
Quantity Per	carton

Product Description

Connector Clips are designed with various fixing point designs, to accommodate the many connectors out in the market. This specific connector clip is designed for a commonly used automotive connector. The width and the height of the fixation point creates minimal rattle when secured. The innovative design of the fir tree creates an interface with four different size holes that are common in the automotive industry. The fir tree branch design on all four sides makes a 360-degree interface with the panel, creating a more secure fit into the hole.

Short Description

Connector Clip, Mounting Hole Dia. 9.0–17.0mm, PA66HIRHS, Black, 2000/carton

Global Part Name

CC20-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial)

35.0

Minimum Tensile Strength (Metric)

155

Length L (Imperial)

1.00

Length L (Metric)

25.5

Fixation Method

Fir Tree

Width W (Imperial)

0.80

Width W (Metric)

20.3

Height H (Imperial)

1.03

Height H (Metric)

26.1

Panel Thickness Min(Imperial)

0.02

Panel Thickness Max(Imperial)

0.37

Panel Thickness Min (Metric) 0.6

Panel Thickness Max (Metric) 9.5

Mounting Hole Diameter D (Imperial) 0.35 " x 0.67

Mounting Hole Diameter D (Metric) 9.0 x 17.0 mm

Mounting Hole Diameter D Min (Imperial) 0.35

Mounting Hole Diameter D Max (Imperial) 0.67

Mounting Hole Diameter D Max (Metric) 17.0

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL 94 HB

Operating Temperature (Metric) -40°F to +230°F (-40°C to +110°C)

Package Quantity(Imperial) 2000

Package Quantity (Metric) 2000

Customs Number 3926909987

© 2019 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)