

## Specification Sheet

Part Number: 151-01397



Connector Clip, Mounting Hole Dia. 9.0–17.0mm, PA66HIRHSUV, Black, 2000/carton

Article Number	151-01397
Type	CC20
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>• Connector clip design to meet USCAR EWCAP-005-7 clip slot specifications, assuring compliance.</li><li>• Meets installation and extration requirements of SAE/USCAR-2, delivering easy insertion with reliable performance.</li><li>• Long fir tree designed for use in thicker panels up to 9.5 mm.</li><li>• Oval fir tree prevents rotation in 9x17 mm holes.</li></ul>
Quantity Per	carton

**Product Description**

Connector Clips are designed with various fixing point designs, to accommodate the many connectors out in the market. This specific connector clip is designed for a commonly used automotive connector. The width and the height of the fixation point creates minimal rattle when secured. The innovative design of the fir tree creates an interface with four different size holes that are common in the automotive industry. The fir tree branch design on all four sides makes a 360-degree interface with the panel, creating a more secure fit into the hole.

**Short Description**

Connector Clip, Mounting Hole Dia. 9.0–17.0mm, PA66HIRHSUV, Black, 2000/carton

**Global Part Name**

CC20-PA66HIRHSUV-BK

**Minimum Tensile Strength (Imperial)**

35.0

**Minimum Tensile Strength (Metric)**

155

**Length L (Imperial)**

1.00

**Length L (Metric)**

25.5

**Fixation Method**

Fir Tree

**Width W (Imperial)**

0.80

**Width W (Metric)**

20.3

**Height H (Imperial)**

1.03

**Height H (Metric)**

26.1

**Panel Thickness Min(Imperial)**

0.02

**Panel Thickness Max(Imperial)**

0.37

**Panel Thickness Min (Metric)** 0.6

**Panel Thickness Max (Metric)** 9.5

**Mounting Hole Diameter D (Imperial)** 0.35 " x 0.67

**Mounting Hole Diameter D (Metric)** 9.0 x 17.0 mm

**Mounting Hole Diameter D Min (Imperial)** 0.35

**Mounting Hole Diameter D Max (Imperial)** 0.67

**Mounting Hole Diameter D Max (Metric)** 17.0

**Material** Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

**Material Shortcut** PA66HIRHSUV

**Flammability** UL 94 HB

**Operating Temperature (Metric)** -40°F to +221°F (-40°C to +105°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Package Quantity(Imperial)** 2000

**Package Quantity (Metric)** 2000

**Customs Number**

3926909988

**Content Unit(BMEcat)**

pcs.