

Specification Sheet

Part Number: 151-01535



The H-profile provides a broad surface contact to minimize the pinching of bundles

Heavy duty fir tree mounts are equipped with a friction tab that will hold the tie in the mount, allowing them to be preassembled prior to installation

Designed specifically for HellermannTyton 120 - 250 lb cable ties for heavy duty applications

Heavy Duty Fir Tree Mount, Mounting Hole Dia. 9.0x17.0mm, PPS, Silver, 2000/carton

Article Number	151-01535
Type	FT9X17LGB
Color	Silver (SR)
Quantity Per	carton
Product Description	HellermannTyton heavy duty fir-tree mounts are designed with heavy duty applications in mind. These are optimized for up to 3-to-1 extraction versus insertion force to make assembly fast and easy.
Short Description	Heavy Duty Fir Tree Mount, Mounting Hole Dia. 9.0x17.0mm, PPS, Silver, 2000/carton
Global Part Name	FT9X17LGB-PPS-SR

Length L (Imperial)	1.00
Length L (Metric)	25.50
Fixation Method	Fir Tree for oval holes
Width W (Imperial)	0.80
Width W (Metric)	20.32
Height H (Imperial)	0.99
Height H (Metric)	25.25
Panel Thickness Min (Imperial)	0.023
Panel Thickness Max (Imperial)	0.37
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	9.5
Mounting Hole Diameter D (Imperial)	0.35 x 0.67
Mounting Hole Diameter D (Metric)	9.0 x 17.0 mm
Mounting Hole Diameter D Min (Imperial)	0.35
Mounting Hole Diameter D Max (Imperial)	0.67
Mounting Hole Diameter D Max (Metric)	17.0

Material	Polyphenylene Sulfide (PPS)
Material Shortcut	PPS
UV Resistant (Yes/No)	No
Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Package Quantity (Imperial)	2000
Package Quantity (Metric)	2000
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)