

Specification Sheet

Part Number: 151-01535

The H-profile provides a broad surface contact to minimize the pinching of bundles

Heavy duty fir tree mounts are equipped with a friction tab that will hold the tie in the mount, allowing them to be preassembled prior to installation



Designed specifically for HellermannTyton 120 - 250 lb cable ties for heavy duty applications

Heavy Duty Fir Tree Mount, Mounting Hole Dia. 9.0x17.0mm, PPS, Silver, 2000/carton

Article Number 151-01535

Type FT9X17LGB

Color Silver (SR)

Quantity Per carton

Product Description HellermannTyton heavy duty fir-tree mounts are designed with heavy duty applications in mind. These are optimized for up to 3-to-1 extraction versus insertion force to make assembly fast and easy.

Short Description Heavy Duty Fir Tree Mount, Mounting Hole Dia. 9.0x17.0mm, PPS, Silver, 2000/carton

Global Part Name FT9X17LGB-PPS-SR

Length L (Imperial)	1.00
Length L (Metric)	25.50
Fixation Method	Fir Tree for oval holes
Width W (Imperial)	0.80
Width W (Metric)	20.32
Height H (Imperial)	0.99
Height H (Metric)	25.25
Panel Thickness Min (Imperial)	0.023
Panel Thickness Max (Imperial)	0.37
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	9.5
Mounting Hole Diameter D (Imperial)	0.35 x 0.67
Mounting Hole Diameter D (Metric)	9.0 x 17.0 mm
Mounting Hole Diameter D Min (Imperial)	0.35
Mounting Hole Diameter D Max (Imperial)	0.67
Mounting Hole Diameter D Max (Metric)	17.0

Material	Polyphenylene Sulfide (PPS)
Material Shortcut	PPS
Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Package Quantity (Imperial)	2000
Package Quantity (Metric)	2000
Customs Number	3926909988

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)