

Specification Sheet

Part Number: 151-01538



The fir tree branch design on all four sides makes a 360-degree interface with the panel, creating a more secure fit into the hole. The disc on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

The oval hole fir tree fits 4 common automotive oval hole sizes.

The specific connector slot on this part reduces rattle and movement of clip to the wire harness connector.

Connector Clip w/Oval Fir Tree, Hole Dia. Dia. 6.2–13.0mm, PPS, Silver 5000/carton

Article Number 151-01538

Type CCOVAL

Color Silver (SR)

Quantity Per carton

Product Description Connector Clips are designed with various fixing point designs, to accommodate the many connectors out in the market. This specific connector clip is designed for a commonly used automotive connector. The width and the height of the fixation point creates minimal rattle when secured. The innovative design of the fir tree creates an interface with four different size holes that are common in the automotive industry. The fir tree branch design on all four sides makes a 360-degree interface with the panel, creating a more secure fit into the hole.

| | |
|---|--|
| Short Description | Connector Clip w/Oval Fir Tree, Hole Dia. Dia. 6.2–13.0mm, PPS, Silver 5000/carton |
| Global Part Name | CCOVAL-PPS-SR |
| Length L (Imperial) | 1.16 |
| Length L (Metric) | 29.34 |
| Fixation Method | Fir Tree for oval holes |
| Width W (Imperial) | 0.69 |
| Width W (Metric) | 17.63 |
| Height H (Imperial) | 0.79 |
| Height H (Metric) | 19.98 |
| Panel Thickness Min (Imperial) | 0.023 |
| Panel Thickness Max (Imperial) | 0.27 |
| Panel Thickness Min (Metric) | 0.6 |
| Panel Thickness Max (Metric) | 6.75 |
| Mounting Hole Diameter D (Imperial) | 0.24 x 0.48 " 0.26 x 0.50 " 0.26 x 0.51 " 0.28 x 0.47 |
| Mounting Hole Diameter D (Metric) | 7.0 x 12.0 mm 6.5 x 13.0 mm 6.5 x 12.5 mm 6.2 x 12.2 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.24 |

Mounting Hole Diameter D Max (Imperial) 0.51

Mounting Hole Diameter D Max (Metric) 13.0

Material Polyphenylene Sulfide (PPS)

Material Shortcut PPS

UV Resistant (Yes/No) No

Operating Temperature -40°F to +302°F (-40°C to +150°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 5000

Package Quantity (Metric) 5000

Customs Number 3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)