

## Specification Sheet

Part Number: 151-01538



The fir tree branch design on all four sides makes a 360-degree interface with the panel, creating a more secure fit into the hole.

The disc on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

The oval hole fir tree fits 4 common automotive oval hole sizes.

The specific connector slot on this part reduces rattle and movement of clip to the wire harness connector.

Connector Clip w/Oval Fir Tree, Hole Dia. Dia. 6.2–13.0mm, PPS, Silver 5000/carton

**Article Number** 151-01538

**Type** CCOVAL

**Color** Silver (SR)

**Quantity Per** carton

<b>Product Description</b>	Connector Clips are designed with various fixing point designs, to accommodate the many connectors out in the market. This specific connector clip is designed for a commonly used automotive connector. The width and the height of the fixation point creates minimal rattle when secured. The innovative design of the fir tree creates an interface with four different size holes that are common in the automotive industry. The fir tree branch design on all four sides makes a 360-degree interface with the panel, creating a more secure fit into the hole.
<b>Short Description</b>	Connector Clip w/Oval Fir Tree, Hole Dia. Dia. 6.2–13.0mm, PPS, Silver 5000/carton
<b>Global Part Name</b>	CCOVAL-PPS-SR
<b>Length L (Imperial)</b>	1.16
<b>Length L (Metric)</b>	29.34
<b>Fixation Method</b>	Fir Tree for oval holes
<b>Width W (Imperial)</b>	0.69
<b>Width W (Metric)</b>	17.63
<b>Height H (Imperial)</b>	0.79
<b>Height H (Metric)</b>	19.98
<b>Panel Thickness Min (Imperial)</b>	0.023
<b>Panel Thickness Max (Imperial)</b>	0.27
<b>Panel Thickness Min (Metric)</b>	0.6

<b>Panel Thickness Max (Metric)</b>	6.75
<b>Mounting Hole Diameter D (Imperial)</b>	0.24 x 0.48 " 0.26 x 0.50 " 0.26 x 0.51 " 0.28 x 0.47
<b>Mounting Hole Diameter D (Metric)</b>	7.0 x 12.0 mm 6.5 x 13.0 mm 6.2 x 12.2 mm 6.5 x 12.5 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.24
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.51
<b>Mounting Hole Diameter D Max (Metric)</b>	13.0

**Material** Polyphenylene Sulfide (PPS)

**Material Shortcut** PPS

**Operating Temperature** -40°F to +302°F (-40°C to +150°C)

**Reach Compliant (Article 33)** Yes

**ROHS Compliant** Yes

**Package Quantity (Imperial)** 5000

**Package Quantity (Metric)** 5000

**Customs Number** 3926909988

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)