


Specification Sheet

Part Number: 151-01629



High Heat High Bond Acrylic Adh Base, 0.75" x 0.75", Use T18-T30 Tie, PA66HIRHSUV, Black, 100/pkg

Article Number 151-01629

Type MB3A

Color Black (BK)

Features & Benefits

- For use with HellermannTyton T18 - T30 cable ties to provide stability when securing bundles.
- 4-way opening allows cable ties to be installed parallel or perpendicular to bundles.
- The high-heat, high-bond adhesive is ideal for outdoor applications, with a static load weight of 0.6 lb.
- Two predrilled holes extend mounting options and solutions.
- Extended adhesive liner is easy to remove quickly.

Quantity Per bag

Product Description	MB3A4 adhesive mounts are for use with HellermannTyton T18 - T30 Series cable ties to provide stability when securing bundles. The high-heat, high-bond acrylic adhesive-backed mounts can be used to secure a bundle and have two predrilled holes to extend mounting options.
Short Description	High Heat High Bond Acrylic Adh Base, 0.75" x 0.75", Use T18-T30 Tie, PA66HIRHSUV, Black, 100/pkg
Global Part Name	MB3A-PA66HIRHSUV-BK
Length L (Imperial)	0.75
Length L (Metric)	19.0
Fixation Method	Screw Mounting and Adhesive
Width W (Imperial)	0.75
Width W (Metric)	19.0
Cable Ties	T18 - T30
Height H (Imperial)	.19
Height H (Metric)	4.8
Cable Tie Width Max (Imperial)	0.14
Cable Tie Width Max (Metric)	3.6
Mounting Hole Diameter D (Imperial)	0.12

Mounting Hole Diameter D (Metric) 3.0 mm

Mounting Hole Diameter D Min (Imperial) 0.12

Mounting Hole Diameter D Max (Imperial) 0.12

Mounting Hole Diameter D Max (Metric) 3.0

Mounting Hole Centers (Imperial) 0.52

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Adhesive Acrylic foam

Flammability UL 94 HB (excluding adhesive)

Adhesive Operating Temperature -40°F to +176°F (-40°C to +80°C)

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS Compliant Yes

Package Quantity (Imperial) 100

Package Quantity (Metric) 100

Customs Number

3926909988

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)