


## Specification Sheet

Part Number: 151-01629



High Heat High Bond Acrylic Adh Base, 0.75" x 0.75", Use T18-T30 Tie, PA66HIRHSUV, Black, 100/pkg

**Article Number** 151-01629

**Type** MB3A

**Color** Black (BK)

### Features & Benefits

- For use with HellermannTyton T18 - T30 cable ties to provide stability when securing bundles.
- 4-way opening allows cable ties to be installed parallel or perpendicular to bundles.
- The high-heat, high-bond adhesive is ideal for outdoor applications, with a static load weight of 0.6 lb.
- Two predrilled holes extend mounting options and solutions.
- Extended adhesive liner is easy to remove quickly.

**Quantity Per** bag

<b>Product Description</b>	MB3A4 adhesive mounts are for use with HellermannTyton T18 - T30 Series cable ties to provide stability when securing bundles. The high-heat, high-bond acrylic adhesive-backed mounts can be used to secure a bundle and have two predrilled holes to extend mounting options.
<b>Short Description</b>	High Heat High Bond Acrylic Adh Base, 0.75" x 0.75", Use T18-T30 Tie, PA66HIRHSUV, Black, 100/pkg
<b>Global Part Name</b>	MB3A-PA66HIRHSUV-BK
<b>Length L (Imperial)</b>	0.75
<b>Length L (Metric)</b>	19.0
<b>Fixation Method</b>	Screw Mounting and Adhesive
<b>Width W (Imperial)</b>	0.75
<b>Width W (Metric)</b>	19.0
<b>Cable Ties</b>	T18 - T30
<b>Height H (Imperial)</b>	.19
<b>Height H (Metric)</b>	4.8
<b>Cable Tie Width Max (Imperial)</b>	0.14
<b>Cable Tie Width Max (Metric)</b>	3.6
<b>Mounting Hole Diameter D (Imperial)</b>	0.12

**Mounting Hole Diameter D (Metric)** 3.0 mm

**Mounting Hole Diameter D Min (Imperial)** 0.12

**Mounting Hole Diameter D Max (Imperial)** 0.12

**Mounting Hole Diameter D Max (Metric)** 3.0

**Mounting Hole Centers (Imperial)** 0.52

**Material** Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

**Material Shortcut** PA66HIRHSUV

**Adhesive** Acrylic foam

**Flammability** UL 94 HB (excluding adhesive)

**Adhesive Operating Temperature** -40°F to +176°F (-40°C to +80°C)

**Operating Temperature** -40°F to +221°F (-40°C to +105°C)

**ROHS Compliant** Yes

**Package Quantity (Imperial)** 100

**Package Quantity (Metric)** 100

**Customs Number**

3926909988

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)