

## Specification Sheet

Part Number: 151-01633

For use with HellermannTyton T18 - T150 cable ties to provide stability when securing bundles.

4-way opening allows cable ties to be installed parallel or perpendicular to bundles.

The high-heat, high-bond adhesive is ideal for outdoor applications, with a static load weight of 2.1 lb.

Two predrilled holes extend mounting options and solutions.

Extended adhesive liner is easy to remove quickly.



High Heat High Bond Acrylic Adh Base, 1.49" x 1.49", Use T18-T150 Tie, PA66HIRHSUV, Black, 100/pkg

Article Number 151-01633

Type MB5A4

Color Black (BK)

Quantity Per bag

Product Description MB5A4 adhesive mounts are for use with HellermannTyton T18 - T150 Series cable ties to provide stability when securing bundles. The high-heat, high-bond acrylic adhesive-backed mounts can be used to secure a bundle and have two predrilled holes to extend mounting options.

|   |  |
|---|--|
| Short Description                       | High Heat High Bond Acrylic Adh Base, 1.49" x 1.49", Use T18-T150 Tie, PA66HIRHSUV, Black, 100/pkg |
| Global Part Name                        | MB5A4-PA66HIRHSUV-BK   |
| Length L (Imperial)                     | 1.49   |
| Length L (Metric)                       | 37.7   |
| Fixation Method                         | Screw Mounting and Adhesive  |
| Width W (Imperial)                      | 1.49   |
| Width W (Metric)                        | 37.7   |
| Cable Ties                              | T18 - T150   |
| Height H (Imperial)                     | .28  |
| Height H (Metric)                       | 7.1  |
| Cable Tie Width Max (Imperial)          | 0.35   |
| Cable Tie Width Max (Metric)            | 8.9  |
| Mounting Hole Diameter D (Imperial)     | 0.19   |
| Mounting Hole Diameter D (Metric)       | 4.8 mm   |
| Mounting Hole Diameter D Min (Imperial) | 0.19   |
| Mounting Hole Diameter D Max (Imperial) | 0.19   |

|                                       |  |
|---------------------------------------|--|
| Mounting Hole Diameter D Max (Metric) | 4.8  |
| Mounting Hole Centers (Imperial)      | 1  |
| Material                              | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut                     | PA66HIRHSUV  |
| Adhesive                              | Acrylic foam   |
| Flammability                          | UL 94 HB   |
| UV Resistant (Yes/No)                 | Yes  |
| Adhesive Operating Temperature        | -40°F to +176°F (-40°C to +80°C)   |
| Operating Temperature                 | -40°F to +221°F (-40°C to +105°C)  |
| Reach Compliant (Article 33)          | No   |
| ROHS Compliant                        | Yes  |
| Package Quantity (Imperial)           | 100  |
| Package Quantity (Metric)             | 100  |
| Customs Number                        | 3926909988   |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)