

## Specification Sheet

Part Number: 151-01768



MOC Clip, 14 mm, with 6.5mm Fir Tree, PA66HIRHSUV, Black, 3000/ctn

Article Number	151-01768
Type	MOC14FT6.5
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>• Patented retention design features inverted retaining legs, narrow opening and circular retainer to prevent inadvertent disengagement.</li><li>• Controlled flex and angled entry promote easy installation.</li><li>• Fir tree demonstrates easy insertion with high extraction resistance.</li></ul>
Quantity Per	carton
Product Description	The MOC with Round Fir Tree features HellermannTyton's unique retention clip with an integrated fir tree to fit securely in a 6.5 (+/-0.4) mm hole. The mount delivers a low insertion force while exhibiting high extraction resistance for a secure mounting point against a panel.
Short Description	MOC Clip, 14 mm, with 6.5mm Fir Tree, PA66HIRHSUV, Black, 3000/ctn

Global Part Name

MOC14FT6.5-PA66HIRHSUV-BK

Length L (Imperial)

0.82

Length L (Metric)

20.9

Fixation Method

Fir Tree

Bundle Diameter Min (Imperial)

0.51

Bundle Diameter Min (Metric)

13.5

Bundle Diameter Max (Imperial)

0.62

Bundle Diameter Max (Metric)

15.8

Height H (Imperial)

1.55

Height H (Metric)

39.3

Depth D (imperial)

0.39

Depth D (metric)

10.0

Panel Thickness Min(Imperial)

0.02

Panel Thickness Max(Imperial)

0.22

Panel Thickness Min (Metric)

0.60

Panel Thickness Max (Metric)

5.5

Mounting Hole Diameter D (Imperial)

0.25 " HEX; 0.26

<b>Mounting Hole Diameter D (Metric)</b>	6.35 mm (hexagonal) 6.5 mm (+/- 0.4 mm)
<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL 94 HB
<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-40°F to +230°F (-40°C to +110°C)
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	3000
<b>Package Quantity (Metric)</b>	3000
<b>Customs Number</b>	3926909988
<b>Weight (Metric)</b>	1.64
<b>Weight (Imperial)</b>	0.06

