

## Specification Sheet

Part Number: 151-01829



MOC Clip, 26 mm, with 4 x Oval Fir Tree, PA66HIRHSUV, Black, 1000/ctn

<b>Article Number</b>	151-01829
<b>Type</b>	MOC26FTOVAL
<b>Color</b>	Black (BK)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Patented retention design features inverted retaining legs, narrow opening and circular retainer to prevent inadvertent disengagement. •</li><li>Controlled flex and angled entry promote easy installation. •</li><li>Non-rotating fir tree demonstrates easy insertion with high extraction resistance.</li></ul>
<b>Quantity Per</b>	carton

<b>Product Description</b>	The MOC with Oval Fir Tree features HellermannTyton's unique retention clip attached to a 4x oval fir tree that will not rotate in the mounting hole. The mount delivers a low insertion force while exhibiting high extraction resistance for a secure mounting point against a panel. This one design exceeds automotive requirements for the four most common oval sizes: 6.2x12.2 mm, 6.5x12.5 mm, 6.5x13 mm and 7x12 mm.
<b>Short Description</b>	MOC Clip, 26 mm, with 4 x Oval Fir Tree, PA66HIRHSUV, Black, 1000/ctn
<b>Global Part Name</b>	MOC26FTOVAL-PA66HIRHSUV-BK
<b>Length L (Imperial)</b>	1.36
<b>Length L (Metric)</b>	34.5
<b>Fixation Method</b>	Fir Tree
<b>Bundle Diameter Min (Imperial)</b>	0.91
<b>Bundle Diameter Min (Metric)</b>	23.0
<b>Bundle Diameter Max (Imperial)</b>	1.14
<b>Bundle Diameter Max (Metric)</b>	29.0
<b>Height H (Imperial)</b>	2.29
<b>Height H (Metric)</b>	58.1
<b>Depth D (imperial)</b>	0.47

<b>Depth D (metric)</b>	12.0
<b>Panel Thickness Min(Imperial)</b>	0.02
<b>Panel Thickness Max(Imperial)</b>	0.27
<b>Panel Thickness Min (Metric)</b>	0.60
<b>Panel Thickness Max (Metric)</b>	6.75
<b>Mounting Hole Diameter D (Imperial)</b>	0.24 x 0.48"; 0.26 x 0.49"; 0.26 x 0.51"; 0.28 x 0.47 "; 0.27" x 0.47
<b>Mounting Hole Diameter D (Metric)</b>	6.5 x 12.5 mm 6.2 x 12.2 mm 7.0 x 12.0 mm 6.5 x 13.0 mm
<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL 94 HB
<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-40°F to +230°F (-40°C to +110°C)
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	1000

**Package Quantity (Metric)** 1000

**Customs Number** 3926909988

**Weight (Metric)** 4.33

**Weight (Imperial)** 0.15