

Specification Sheet

Part Number: 151-01829



Patented retention design features inverted retaining legs, narrow opening and circular retainer to prevent inadvertent disengagement. Controlled flex and angled entry promote easy installation.

Non-rotating fir tree demonstrates easy insertion with high extraction resistance.

MOC Clip, 26 mm, with 4 x Oval Fir Tree, PA66HIRHSUV, Black, 1000/ctn

Article Number 151-01829

Type MOC26FTOVAL

Color Black (BK)

Quantity Per bag

Product Description The MOC with Oval Fir Tree features HellermannTyton's unique retention clip attached to a 4x oval fir tree that will not rotate in the mounting hole. The mount delivers a low insertion force while exhibiting high extraction resistance for a secure mounting point against a panel. This one design exceeds automotive requirements for the four most common oval sizes: 6.2x12.2 mm, 6.5x12.5 mm, 6.5x13 mm and 7x12 mm.

Short Description MOC Clip, 26 mm, with 4 x Oval Fir Tree, PA66HIRHSUV, Black, 1000/ctn

Global Part Name MOC26FTOVAL-PA66HIRHSUV-BK

Length L (Imperial) 1.36

Length L (Metric) 34.5

Fixation Method Fir Tree

Bundle Diameter Min (Imperial) 0.91

Bundle Diameter Min (Metric) 23.0

Bundle Diameter Max (Imperial) 1.14

Bundle Diameter Max (Metric) 29.0

Height H (Imperial) 2.29

Height H (Metric) 58.1

Depth D (Imperial) 0.47

Depth D (Metric) 12.0

Panel Thickness Min (Imperial) 0.02

Panel Thickness Max (Imperial) 0.27

Panel Thickness Min (Metric) 0.60

Panel Thickness Max (Metric) 6.75

Mounting Hole Diameter D (Imperial)	0.24 x 0.48 "; 0.26 x 0.49 "; 0.26 x 0.51 "; 0.28 x 0.47 "; 0.27" x 0.47
Mounting Hole Diameter D (Metric)	6.2 x 12.2 mm 7.0 x 12.0 mm 6.5 x 13.0 mm 6.5 x 12.5 mm
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988