

Specification Sheet

Part Number: 151-01869

Connector Clips provide a simple and easy method for mounting connectors to a mounting surface in a variety of applications. HellermannTyton offers connector clips with robust and detailed designs that include anti-rattle disc features, anti-rotation oval fir trees, and clamps for mounting on edges.



HellermannTyton offers an assortment of connector clips that are available for a variety of connector slot designs found on most of the largest global connector manufacturers.

Connector Clip, Hole Dia. 6.5(+/- 0.2)mm, Panel 0.7-1.3mm, PA66HIRHS, Black, 500/Pack

Article Number	151-01869
Type	YCCKSFT6.5
Color	Black (BK)
Quantity Per	bag
Product Description	Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description	Connector Clip, Hole Dia. 6.5(+/- 0.2)mm, Panel 0.7-1.3mm, PA66HIRHS, Black, 500/Pack
Global Part Name	YCCKSFT6.5-PA66HIRHS-BK
Length L (Imperial)	1.06
Length L (Metric)	27.0
Fixation Method	Arrowhead (Small Mount)
Height H (Imperial)	0.43
Height H (Metric)	10.9
Panel Thickness Min (Imperial)	0.03
Panel Thickness Max (Imperial)	0.05
Panel Thickness Min (Metric)	0.7
Panel Thickness Max (Metric)	1.3
Mounting Hole Diameter D (Imperial)	0.25-0.26
Mounting Hole Diameter D (Metric)	6.3 - 6.7 mm
Mounting Hole Diameter D Min (Imperial)	0.25
Mounting Hole Diameter D Max (Imperial)	0.26

Mounting Hole Diameter D Max (Metric) 6.7

Material Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut PA66HIRHS

Flammability UL 94 HB

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988