


Specification Sheet

Part Number: 151-01884



The different fixing orientations allow tape clips to be used with a wide range of panel thicknesses and hole diameters.

Bundling Clip w/Oval Fir Tree, 1.52" L, 0.02 - 0.10" Panel Thickness, PA66HIRHS, Natural, 8000/ctn

| | |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number | 151-01884 |
| Type | BCSFTOVAL2 |
| Color | Natural (NA) |
| Quantity Per | carton |
| Product Description | HellermannTyton Bundling Clips are designed to provide simple and easy methods for securing cable bundles, hoses, or pipes. They are fastened onto the tape bar using tape or cable ties. |
| Short Description | Bundling Clip w/Oval Fir Tree, 1.52" L, 0.02 - 0.10" Panel Thickness, PA66HIRHS, Natural, 8000/ctn |
| Global Part Name | BCSFTOVAL2-PA66HIRHS-NA |

| | |
|-----------------------------------------|---------------------------------------------------------|
| Minimum Tensile Strength (Imperial) | 25 |
| Minimum Tensile Strength (Metric) | 110 |
| Length L (Imperial) | 1.52 |
| Length L (Metric) | 38.7 |
| Fixation Method | Fir Tree for oval holes |
| Width W (Imperial) | 0.30 |
| Width W (Metric) | 7.62 |
| Height H (Imperial) | 0.46 |
| Height H (Metric) | 11.6 |
| Panel Thickness Min (Imperial) | 0.02 |
| Panel Thickness Max (Imperial) | 0.10 |
| Panel Thickness Min (Metric) | 0.6 |
| Panel Thickness Max (Metric) | 2.5 |
| Mounting Hole Diameter D (Imperial) | 0.24 x 0.48 ";0.25 x 0.50 ";0.25 x 0.50 ";0.27 x 0.47 |
| Mounting Hole Diameter D (Metric) | 6.5 x 12.5 mm 6.5 x 13.0 mm 6.2 x 12.2 mm 7.0 x 12.0 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.24 |

Mounting Hole Diameter D Max (Imperial) 0.50

Mounting Hole Diameter D Max (Metric) 13.0

Material Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut PA66HIRHS

Flammability UL 94 HB

UV Resistant (Yes/No) No

Operating Temperature -40°F to +230°F (-40°C to +110°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 8000

Package Quantity (Metric) 8000

Customs Number 3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach

to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)