

Specification Sheet

Part Number: 151-02051



Connector Clip, Mounting Hole Dia. 6.2–13.0mm, PA66HIRHS, Black, 5000/carton

Article Number	151-02051
Type	CC22
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• HellermannTyton's 4x oval fir tree prevents bundle rotation while providing best-in-class installation and extraction resistance for four common oval sizes.• Angled connector clip allows for clearance from obstructions and sheet metal contours.• Connector clip design meets USCAR EWCAP-005-11 clip slot specifications, assuring compliance.
Quantity Per	carton

Product Description

Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description	Connector Clip, Mounting Hole Dia. 6.2–13.0mm, PA66HIRHS, Black, 5000/carton
Global Part Name	CC22-PA66HIRHSUV-BK
Length L (Imperial)	1.01
Length L (Metric)	25.71
Fixation Method	Fir Tree
Width W (Imperial)	0.69
Width W (Metric)	17.53
Panel Thickness Min(Imperial)	0.02
Panel Thickness Max(Imperial)	0.27
Panel Thickness Min (Metric)	0.51
Panel Thickness Max (Metric)	6.75
Mounting Hole Diameter D (Imperial)	0.24 x 0.48 " 0.26 x 0.50 " 0.26 x 0.51 " 0.28 x 0.47
Mounting Hole Diameter D (Metric)	7.0 x 12.0 mm 6.5 x 13.0 mm 6.2 x 12.2 mm 6.5 x 12.5 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.51
Mounting Hole Diameter D Max (Metric)	13.0

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +230°F (-40°C to +110°C)
ROHS Complaint	Yes
Package Quantity(Imperial)	5000
Package Quantity (Metric)	5000