

## Specification Sheet

Part Number: 151-02051

HellermannTyton's 4x oval fir tree prevents bundle rotation while providing best-in-class installation and extraction resistance for four common oval sizes.

Angled connector clip allows for clearance from obstructions and sheet metal contours.



Connector clip design meets USCAR EWCAP-005-11 clip slot specifications, assuring compliance.

Connector Clip, 6.2–13.0mm Hole Dia., PA66HIRHSUV, Black, 5000/carton

**Article Number** 151-02051

**Type** CC22

**Color** Black (BK)

**Quantity Per** carton

**Product Description** Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

<b>Short Description</b>	Connector Clip, 6.2–13.0mm Hole Dia., PA66HIRHSUV, Black, 5000/carton
<b>Global Part Name</b>	CC22-PA66HIRHSUV-BK
<b>Length L (Imperial)</b>	1.01
<b>Length L (Metric)</b>	25.71
<b>Fixation Method</b>	Fir Tree
<b>Width W (Imperial)</b>	0.69
<b>Width W (Metric)</b>	17.53
<b>Height H (Metric)</b>	26.0
<b>Panel Thickness Min (Imperial)</b>	0.02
<b>Panel Thickness Max (Imperial)</b>	0.27
<b>Panel Thickness Min (Metric)</b>	0.51
<b>Panel Thickness Max (Metric)</b>	6.75
<b>Mounting Hole Diameter D (Imperial)</b>	0.24 x 0.48 " 0.26 x 0.50 " 0.26 x 0.51 " 0.28 x 0.47
<b>Mounting Hole Diameter D (Metric)</b>	6.5 x 12.5 mm 6.5 x 13.0 mm 6.2 x 12.2 mm 7.0 x 12.0 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.24

**Mounting Hole Diameter D Max (Imperial)** 0.51

**Mounting Hole Diameter D Max (Metric)** 13.0

**Material** Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

**Material Shortcut** PA66HIRHSUV

**Flammability** UL 94 HB

**Operating Temperature** -40°F to +221°F (-40°C to +105°C)

**Reach Compliant (Article 33)** No

**ROHS Compliant** Yes

**Package Quantity (Imperial)** 5000

**Package Quantity (Metric)** 5000

**Customs Number** 3926909988