

## Specification Sheet

Part Number: 151-02076

HellermannTyton connector clips provide a simple and easy method for mounting connectors to a mounting surface in a variety of applications. Detailed designs include anti-rattle disc features, anti-rotation oval fir trees, and clamps for mounting on edges.

HellermannTyton offers an assortment of connector clips that are available for a variety of connector slot designs found on most of the largest global connector manufacturers.



Conn. Clip w/Arrowhead, 0.7-3.0mm Panel Thick., 6.5 x 13.0mm Hole Dia., PA66HIRHSUV, Black, 5000/box

Article Number 151-02076

Type CCIVSFT6.5x130

Color Black (BK)

Quantity Per bag

Product Description Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description	Conn. Clip w/Arrowhead, 0.7-3.0mm Panel Thick., 6.5 x 13.0mm Hole Dia., PA66HIRHSUV, Black, 5000/box
Global Part Name	CCIVSFT6.5x130-PA66HIRHSUV-BK
Length L (Imperial)	0.91
Length L (Metric)	23.0
Fixation Method	Arrowhead (Small Mount)
Width W (Imperial)	0.77
Width W (Metric)	19.6
Height H (Imperial)	0.57
Height H (Metric)	41.6
Panel Thickness Min (Imperial)	0.03
Panel Thickness Max (Imperial)	0.12
Panel Thickness Min (Metric)	0.7
Panel Thickness Max (Metric)	3.0
Mounting Hole Diameter D (Imperial)	0.26 " x 0.52
Mounting Hole Diameter D (Metric)	6.5 x 13.0 mm

Mounting Hole Diameter D Min (Imperial) 0.26

Mounting Hole Diameter D Max (Imperial) 0.52

Mounting Hole Diameter D Max (Metric) 13.0

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL 94 HB

Operating Temperature -40°F to +257°F (-40°C to +125°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 5000

Package Quantity (Metric) 5000

Customs Number 3926909988

