

Specification Sheet

Part Number: 151-02076



HellermannTyton connector clips provide a simple and easy method for mounting connectors to a mounting surface in a variety of applications. Detailed designs include anti-rattle disc features, anti-rotation oval fir trees, and clamps for mounting on edges.

HellermannTyton offers an assortment of connector clips that are available for a variety of connector slot designs found on most of the largest global connector manufacturers.

Conn. Clip w/Arrowhead, 0.7-3.0mm Panel Thick., 6.5 x 13.0mm Hole Dia., PA66HIRHSUV, Black, 5000/box

Article Number	151-02076
Type	CCIVSFT6.5x130
Color	Black (BK)
Quantity Per	bag
Product Description	HellermannTyton connector clips, for oval holes, are mounted simply by pushing them onto the corresponding clip. The clips provide a wide range of mounting options with anti-rattle and anti-rotation features. The fir tree locks into place when inserted into the hole palpably and ensures a secure fixing at all times.
Short Description	Conn. Clip w/Arrowhead, 0.7-3.0mm Panel Thick., 6.5 x 13.0mm Hole Dia., PA66HIRHSUV, Black, 5000/box

Global Part Name

CCIVSFT6.5x130-PA66HIRHSUV-BK

Length L (Imperial)

0.91

Length L (Metric)

23.0

Fixation Method

Arrowhead (Small Mount)

Width W (Imperial)

0.77

Width W (Metric)

19.6

Height H (Imperial)

0.57

Height H (Metric)

41.6

Panel Thickness Min (Imperial)

0.03

Panel Thickness Max (Imperial)

0.12

Panel Thickness Min (Metric)

0.7

Panel Thickness Max (Metric)

3.0

Mounting Hole Diameter D (Imperial)

0.26 " x 0.52

Mounting Hole Diameter D (Metric)

6.5 x 13.0 mm

Mounting Hole Diameter D Min (Imperial)

0.26

Mounting Hole Diameter D Max (Imperial)

0.52

Mounting Hole Diameter D Max (Metric) 13.0

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL 94 HB

Operating Temperature -40°F to +257°F (-40°C to +125°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 5000

Package Quantity (Metric) 5000

Customs Number 3926909988