

## Specification Sheet

Part Number: 151-02078

Once installed, perpendicular arrowhead arms reduce movement and will not collapse when exposed to water or load.

Integrated dual seal meets IP65 for protection against water, dust, chemicals, air and sound.

Superior design and high-spec materials maintain routing position to deliver consistent performance in the most rugged applications.

Low-profile design saves 5 mm of height when installed.

Sealed arrowhead meets USCAR11 push in, pull off and sealing standards.



Conn. Clip w/Arrowhead, 0.6-1.1mm Panel Thickness, 6.5mm/6.35mm HEX,PA66HIRHSUV/TPE, Black, 4000/ctn

Article Number 151-02078

Type SRAH6.5CC

Color Black (BK)

Quantity Per bag

Product Description HellermannTyton sealed clips and ties are constructed of engineered nylon with a dual TPE (thermo plastic elastomer) seal. The combination of dual seal and engineered arrowhead provide superior sealing performance for applications where protection from moisture and debris is essential.

Short Description	Conn. Clip w/Arrowhead, 0.6-1.1mm Panel Thickness, 6.5mm/6.35mm HEX,PA66HIRHSUV/TPE, Black, 4000/ctn
Global Part Name	SRAH6.5CC-PA66HIRHSUV/TPE-BK
Length L (Imperial)	0.87
Length L (Metric)	22.3
Fixation Method	Arrowhead
Variant	6.1 - 6.9 mm
Width W (Imperial)	0.87
Width W (Metric)	22.3
Height H (Imperial)	0.57
Height H (Metric)	14.48
Panel Thickness Min (Imperial)	0.024
Panel Thickness Max (Imperial)	0.043
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	1.1
Mounting Hole Diameter D (Imperial)	0.25 " (hexagonal) 0.25
Mounting Hole Diameter D (Metric)	6.5 mm 6.35 mm (hexagonal)

Material	Thermoplastic Elastomer (TPE) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	TPE PA66HIRHSUV
Flammability	UL 94 HB
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	4000
Package Quantity (Metric)	4000
Customs Number	3926909988

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)