

## Specification Sheet

Part Number: 151-02080

Once installed, perpendicular arrowhead arms reduce movement and will not collapse when exposed to water or load.

Integrated dual seal meets IP65 for protection against water, dust, chemicals, air and sound.

Superior design and high-spec materials maintain routing position to deliver consistent performance in the most rugged applications.

Low-profile design saves 5 mm of height when installed.

Sealed arrowhead meets USCAR 44 push in, pull off and sealing standards.



Conn. Clip w/Round Arrowhead, 1.2-1.8mm Panel Thick, 6.5mm/6.35mm HEX, PA66HIRHS/TPE, BK/GY, 4000/ctn

<b>Article Number</b>	151-02080
<b>Type</b>	SRAH6.5D1.4TCC
<b>Color</b>	Gray (GY) Black (BK)
<b>Quantity Per</b>	bag

**Product Description**

HellermannTyton sealed clips and ties are constructed of engineered nylon with a dual TPE (thermo plastic elastomer) seal. The combination of dual seal and engineered arrowhead provide superior sealing performance for applications where protection from moisture and debris is essential.

<b>Short Description</b>	Conn. Clip w/Round Arrowhead, 1.2-1.8mm Panel Thick, 6.5mm/6.35mm HEX, PA66HIRHS/TPE, BK/GY, 4000/ctn
<b>Global Part Name</b>	SRAH6.5D1.4TCC-PA66HIRHS/TPE-BK/GY
<b>Length L (Imperial)</b>	0.87
<b>Length L (Metric)</b>	22.3
<b>Fixation Method</b>	Arrowhead
<b>Variant</b>	6.1 - 6.9 mm
<b>Width W (Imperial)</b>	0.87
<b>Width W (Metric)</b>	22.3
<b>Height H (Imperial)</b>	0.59
<b>Height H (Metric)</b>	15.08
<b>Panel Thickness Min (Imperial)</b>	0.047
<b>Panel Thickness Max (Imperial)</b>	0.07
<b>Panel Thickness Min (Metric)</b>	1.2
<b>Panel Thickness Max (Metric)</b>	1.8
<b>Mounting Hole Diameter D (Imperial)</b>	0.25 " (hexagonal) 0.25

<b>Mounting Hole Diameter D (Metric)</b>	6.5 mm 6.35 mm (hexagonal)
<b>Material</b>	Thermoplastic Elastomer (TPE) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
<b>Material Shortcut</b>	TPE PA66HIRHS
<b>Operating Temperature</b>	-40°F to +230°F (-40°C to +110°C)
<b>Reach Compliant (Article 33)</b>	No
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	4000
<b>Package Quantity (Metric)</b>	4000
<b>Customs Number</b>	3926909988