

Specification Sheet

Part Number: 151-02080



Arrowhead Mount w/ Seal, 1.2 - 1.8mm Panel Thickness, 6.5mm/6.35mm HEX, PA66HIRHS/TPE, Black/Gray, 4000/ctn

Article Number	151-02080
Type	SRAH6.5D1.4TCC
Color	Gray (GY) Black (BK)

Features & Benefits

- Once installed, perpendicular arrowhead arms reduce movement and will not collapse when exposed to water or load.
- Integrated dual seal meets IP65 for protection against water, dust, chemicals, air and sound.
- Superior design and high-spec materials maintain routing position to deliver consistent performance in the most rugged applications.
- Low-profile design saves 5 mm of height when installed.
- Sealed arrowhead meets USCAR44 push in, pull off and sealing standards.

Quantity Per	bag
---------------------	-----

Product Description	HellermannTyton sealed clips and ties are constructed of engineered nylon with a dual TPE (thermo plastic elastomer) seal. The combination of dual seal and engineered arrowhead provide superior sealing performance for applications where protection from moisture and debris is essential.
Short Description	Arrowhead Mount w/ Seal, 1.2 - 1.8mm Panel Thickness, 6.5mm/6.35mm HEX, PA66HIRHS/TPE, Black/Gray, 4000/ctn
Global Part Name	SRAH6.5D1.4TCC-PA66HIRHS/TPE-BK/GY
Length L (Imperial)	0.87
Length L (Metric)	22.3
Fixation Method	Arrowhead
Width W (Imperial)	0.87
Width W (Metric)	22.3
Height H (Imperial)	0.59
Height H (Metric)	15.08
Panel Thickness Min(Imperial)	0.047
Panel Thickness Max(Imperial)	0.07
Panel Thickness Min (Metric)	1.2
Panel Thickness Max (Metric)	1.8

Mounting Hole Diameter D (Imperial)	0.25 " (hexagonal) 0.25
Mounting Hole Diameter D (Metric)	6.35 mm (hexagonal) 6.5 mm
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) Thermoplastic Elastomer (TPE)
Material Shortcut	PA66HIRHS TPE
Operating Temperature (Metric)	-40°F to +230°F (-40°C to +110°C)
ROHS Complaint	Yes
Use Conditions	For Indoor Use Only
Package Quantity(Imperial)	4000
Package Quantity (Metric)	4000
Customs Number	3926909988
Weight (Metric)	0.003
Weight (Imperial)	0.0066138679

