

Specification Sheet

Part Number: 151-02103



Positions bundles off cross members and frame rails to prevent abrasion and chafing.

Metal insert bushing accommodates high-torque installation.

Made with high-impact, heat stabilized, and UV material ideal for trucking and heavy equipment environments.

High Torque Axial Mount, Bolt Hole Dia. 0.510", PA66HIRHSUV, Black, 500/pkg

Article Number 151-02103

Type SAM500B-R

Color Black (BK)

Quantity Per carton

Product Description HellermannTyton's axial oval mount stands off bundles from frame rails and cross members to prevent them from rubbing and chafing. The axial oval mount accommodates cable ties up to 0.5" wide. The hole on the mount was designed to fit a 5/16" bolt.

Short Description High Torque Axial Mount, Bolt Hole Dia. 0.510", PA66HIRHSUV, Black, 500/pkg

Global Part Name SAM500B-R-PA66HIRHSUV-BK

| | |
|---------------------------------------|--|
| Length L (Imperial) | 1.18 |
| Length L (Metric) | 29.9 |
| Fixation Method | Screw Mounting and Rivet |
| Width W (Imperial) | 1.0 |
| Width W (Metric) | 25.0 |
| Height H (Imperial) | 1.77 |
| Height H (Metric) | 44.9 |
| Cable Tie Width Max (Metric) | 12.7 |
| Mounting Hole Diameter D (Imperial) | 0.51 |
| Mounting Hole Diameter D (Metric) | 12.95 mm |
| Mounting Hole Diameter D Max (Metric) | 12.95 |
| Stud Diameter (Metric) | 12.0 mm |
| Material | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut | PA66HIRHSUV |

| | |
|------------------------------|-----------------------------------|
| Flammability | UL 94 HB |
| UV Resistant (Yes/No) | Yes |
| Use Conditions | For Indoor and Outdoor Use |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 500 |
| Package Quantity (Metric) | 500 |
| Customs Number | 3926909988 |