

Specification Sheet

Part Number: 151-02104



High Torque Double Mnt, 4-Way, Mounting Hole .375", Max Torque 114.0 lb - ft, PA66HIRHSUV, Black, 100/pkg

Article Number

151-02104

Type

HDM375BDM4W

Color

Black (BK)

Features & Benefits

- Arched H-profile surface allows for broad surface contact with the bundle, minimizing pinching and crushing of the bundles.
- High torque metal bushing allows for strength in heavy duty applications.
- These mounts contain a small tab inside the mounting hole to temporarily engage the threads which allows assemblers to pre-install the mount on a stud with a washer and nut.

Quantity Per

carton

Product Description

High Torque Double Mounts are designed for use with power assisted impact wrenches and are molded with a metal bushing to withstand the forces required to tighten grade 8 bolts. Mounts are designed for routing multiple bundles with HellermannTyton heavy duty T250, T255, and wide strap cable ties to harness wires and hoses. The bundle is secured directly over the mounting fastener. The arched saddle surface allows for a broad surface contact with the bundle, minimizing pinching and crushing of the bundles. Mounts accept all standard cable ties up to .5" wide.

Short Description

High Torque Double Mnt, 4-Way, Mounting Hole .375", Max Torque 114.0 lb - ft, PA66HIRHSUV, Black, 100/pkg

Global Part Name

HDM375BDM4W-PA66HIRHSUV-BK

Length L (Imperial)

3.50

Length L (Metric)

89.0

Fixation Method

Screw Mounting and Rivet

Width W (Imperial)

1.4

Width W (Metric)

35.6

Height H (Imperial)

0.99

Height H (Metric)

25.2

Cable Tie Width Max (Imperial)

0.5

Cable Tie Width Max (Metric)

12.7

Mounting Hole Diameter D (Imperial)

0.405

Mounting Hole Diameter D (Metric)

10.29 mm

Mounting Hole Diameter D Max (Metric) 10.29

Mounting Hole Centers (Imperial) 0.405

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL 94 HB

Operating Temperature (Metric) -40°F to +230°F (-40°C to +110°C)

Maximum Torque (kgf-cm) 1576.0

Maximum Torque (lbf-ft) 114.0

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Package Quantity(Imperial) 100

Package Quantity (Metric) 100

Content Unit(BMEcat) pcs.

Weight (Metric) 0.0396

Weight (Imperial) 0.0874

© 2019 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)