

Specification Sheet

Part Number: 151-02189

Integrated design allows for easy insertion by hand.

1.5–2mm panel thickness range allows for multiple applications.

Double-compression design that accommodates various sizes of wire and cable.

Presents a high extraction force for withstanding extreme conditions.



Low Profile 90° Metal Edge Clip, 1.5–2.0mm Panel Thickness, 6–6.2mm Cable Range, SS304, 100/bag

Article Number 151-02189

Type MSC90

Color Metal (ML)

Quantity Per bag

Product Description HellermannTyton's 90-Degree Metal Edge Clip provides an excellent alternative to managing wire and PV cables where plastic fasteners are not the preferred method. Designed for effortless insertion, this edge clip also has a high extraction force. The 90-degree configuration secures cables to a panel in a perpendicular orientation. Metal construction tolerates extreme environments, and a low-profile design allows the clip to be installed on a wide variety of module edges.

Short Description	Low Profile 90° Metal Edge Clip, 1.5–2.0mm Panel Thickness, 6–6.2mm Cable Range, SS304, 100/bag
Global Part Name	MSC90-SS304-ML
Length L (Imperial)	0.73
Length L (Metric)	18.44
Width W (Imperial)	0.460
Width W (Metric)	11.57
Bundle Diameter Min (Imperial)	0.161
Bundle Diameter Min (Metric)	4.1
Bundle Diameter Max (Imperial)	0.276
Bundle Diameter Max (Metric)	7.0
Panel Thickness Min (Imperial)	0.06
Panel Thickness Max (Imperial)	0.078
Panel Thickness Min (Metric)	1.5
Panel Thickness Max (Metric)	2.0

Material	Stainless Steel (SS304)
Material Shortcut	SS304
Flammability	Non-burning
Halogen Free	No
Operating Temperature	-112°F to +1000°F (-80°C to +538°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
UL Recognized (US)	Yes
UL Listed (US and Canada)	Yes
UL Recognized (US and Canada)	Yes
UL Listed (US)	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	100
Customs Number	7326908695

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)