

## Specification Sheet

Part Number: 151-02189



Integrated design allows for easy insertion by hand.

1.5–2mm panel thickness range allows for multiple applications.

Double-compression design that accommodates various sizes of wire and cable.

Presents a high extraction force for withstanding extreme conditions.

Low Profile 90° Metal Edge Clip, 1.5–2.0mm Panel Thickness, 6–6.2mm Cable Range, SS304, 100/bag

**Article Number** 151-02189

**Type** MSC90

**Color** Metal (ML)

**Quantity Per** bag

**Product Description** HellermannTyton's 90-Degree Metal Edge Clip provides an excellent alternative to managing wire and PV cables where plastic fasteners are not the preferred method. Designed for effortless insertion, this edge clip also has a high extraction force. The 90-degree configuration secures cables to a panel in a perpendicular orientation. Metal construction tolerates extreme environments, and a low-profile design allows the clip to be installed on a wide variety of module edges.

<b>Short Description</b>	Low Profile 90° Metal Edge Clip, 1.5–2.0mm Panel Thickness, 6–6.2mm Cable Range, SS304, 100/bag
<b>Global Part Name</b>	MSC90-SS304-SR
<b>Length L (Imperial)</b>	0.73
<b>Length L (Metric)</b>	18.44
<b>Width W (Imperial)</b>	0.460
<b>Width W (Metric)</b>	11.57
<b>Panel Thickness Min (Imperial)</b>	0.06
<b>Panel Thickness Max (Imperial)</b>	0.078
<b>Panel Thickness Min (Metric)</b>	1.5
<b>Panel Thickness Max (Metric)</b>	2.0
<b>Material</b>	Stainless Steel (SS304)
<b>Material Shortcut</b>	SS304
<b>Flammability</b>	Non-Burning
<b>Halogen Free</b>	No

<b>Operating Temperature</b>	-112°F to +1000°F (-80°C to +538°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>UL Recognized (US)</b>	Yes
<b>UL Listed (US and Canada)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>UL Listed (US)</b>	Yes
<b>Package Quantity (Imperial)</b>	100
<b>Package Quantity (Metric)</b>	100
<b>Customs Number</b>	7326908695