

Specification Sheet

Part Number: 151-02206

Non-rotating fir tree provides easy insertion with high extraction resistance for 8x14 mm and 8x15 mm oval holes. Meets installation and extraction requirements of SAE/USCAR-2, for easy installation with reliable performance. Short fir tree avoids obstructions on opposite side of panel. Connector clip design meets USCAR EWCAP-005-11 clip slot specifications, assuring compliance.



Connector Clip, 8.0–15.0mm Hole Dia., PA66HIRHSUV, Black, 5000/carton

Article Number 151-02206

Type CC16R

Color Black (BK)

Quantity Per carton

Product Description Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description Connector Clip, 8.0–15.0mm Hole Dia., PA66HIRHSUV, Black, 5000/carton

Global Part Name

CC16R-PA66HIRHSUV-BK

Length L (Imperial)

1.18

Length L (Metric)

30.0

Fixation Method

Fir Tree

Width W (Imperial)

0.72

Width W (Metric)

18.2

Height H (Imperial)

0.92

Height H (Metric)

23.4

Panel Thickness Min (Imperial)

0.02

Panel Thickness Max (Imperial)

0.31

Panel Thickness Min (Metric)

0.6

Panel Thickness Max (Metric)

3.0

Mounting Hole Diameter D (Imperial)

0.33 " x 0.55 " 0.31 " x 0.59

Mounting Hole Diameter D (Metric)

8.0 x 15.0 mm 8.0 x 14.0 mm

Mounting Hole Diameter D Min (Imperial)

0.31

Mounting Hole Diameter D Max (Imperial)

0.59

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	5000
Package Quantity (Metric)	5000
Customs Number	3926909988