

Specification Sheet

Part Number: 151-02418

Angled channel allows specific guidance around corners or obstructions.

U-Shape channel provides three sides of protection for wire or bundle.

High-quality impact modified heat stabilized UV resistant nylon material with high heat resistance.

Protects against abrasion and other environmental factors.



Mini Channel, 3.7" Long, 90° Angle, 1.6" radius angle, PA66HIRHSUV, Black, 300/carton

Article Number 151-02418

Type 90RA1

Color Black (BK)

Quantity Per carton

Product Description HellermannTyton's Mini-Channel family represents a cost-effective, configurable routing solution that protects wires. Pieces are modular and interchangeable, providing high levels of customization. Mini-channels replace engineered channels that are costly to design and develop.

Short Description Mini Channel, 3.7" Long, 90° Angle, 1.6" radius angle, PA66HIRHSUV, Black, 300/carton

Global Part Name	90RA1-PA66HIRHSUV-BK
Length L (Imperial)	3.70
Length L (Metric)	94.0
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	300
Package Quantity (Metric)	300
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)