

Specification Sheet

Part Number: 151-02437



Ratchet P-Clamp, 1.38"-2.01" Bundle Dia, 180° Long, .47X.66 Hole Dia, PA66HIRHSUV, Black, 140/ctn

Article Number

151-02437

Type

RCD180XM12X17SS

Color

Black (BK)

Features & Benefits

- One-piece ratchet closure design allows for easy installation during pre- or final assembly.
- Four sizes and multiple configurations handle a wide range of diameters and applications, reducing part inventory.
- Clamp interior is designed to guide and center bundle to reduce pinching.
- Easy release feature allows for quick adjustments and maintenance.
- Stainless steel mounting plate tolerates high torque mounting, resists galvanic corrosion with dissimilar metals, and harsh chemicals.

Quantity Per

carton

Product Description

The Ratchet P-Clamp family offers versatility when managing wires, cables and hoses. The robust design and durable materials make it ideal for heavy duty applications, both indoors and out. The one-piece adjustable clamp can be closed by hand to the desired diameter. The release feature provides easy and nondestructive removal of cables simply by using a flat-head screwdriver. This nondestructive release allows the clamp to be reused without removing or replacing any bolts or screws. The Ratchet P-Clamp is offered in four sizes and multiple mounting configurations.

Short Description

Ratchet P-Clamp, 1.38"-2.01" Bundle Dia, 180° Long, .47X.66 Hole Dia, PA66HIRHSUV, Black, 140/ctn

Global Part Name

RCD180XM12X17SS-PA66HIRHS/SS304-BK

Minimum Tensile Strength (Imperial)

100.0

Length L (Imperial)

7.69

Length L (Metric)

195.2

Fixation Method

Screw Mounting

Variant

Fixing clamp

Width W (Imperial)

1.37

Width W (Metric)

34.9

Bundle Diameter Min (Imperial)

1.47

Bundle Diameter Min (Metric)

36.0

Bundle Diameter Max (Imperial)

2.0

Bundle Diameter Max (Metric)

51.0

Mounting Hole Diameter D (Imperial) 0.47 " x 0.66

Mounting Hole Diameter D (Metric) 12.0 x 17.0 mm

Material Stainless Steel (SS304) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut SS304 PA66HIRHS

UV Resistant (Yes/No) Yes

Operating Temperature (Metric) -40°F to +221°F (-40°C to +105°C)

ROHS Complaint Yes

UL Listed (US and Canada) Yes

UL Listed (US) Yes

Package Quantity(Imperial) 140

Package Quantity (Metric) 140

Customs Number 3926909988

