

Specification Sheet

Part Number: 151-02501



LOC Locking Clamp, 10–14 mm Bundle Dia with FT9X12 Fir Tree, PA66HIRHSUV, Black, 500/pkg

Article Number	151-02501
Type	LOC1014FT9x12
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• Releasable clamp mechanism allows for easy, one-handed maintenance without removing mount.• Low-insertion, high-extraction fir tree fits 9x12 mm to 9x14 mm oval holes.• Capable of holding multiple cables in clamp and additional cables via an optional cable tie, for ultimate flexibility.• High impact modified, heat-resistant, UV stabilized material is ideal for long-term performance, even in extreme weather.
Quantity Per	bag

Product Description

The Locking Clamp is ideal for fastening wire and cable bundles to panels. Its uniquely engineered fir tree holds tightly in pre-stamped hole sizes from 9x12 mm to 9x14 mm. The locking clamp mechanism dynamically fits various bundle sizes, while an integrated cable tie saddle allows installers to add additional cable runs. The clamp is manufactured of an impact-modified Polyamide 6.6 material for increased flexibility, heat resistance and UV stabilization to deliver years of dependable performance. It is easy to install and operate with a single hand and does not require tools, saving time and labor costs.

Short Description

LOC Locking Clamp, 10–14 mm Bundle Dia with FT9X12 Fir Tree, PA66HIRHSUV, Black, 500/pkg

Global Part Name

LOC1014FT9x12-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

225.0

Length L (Imperial)

1.37

Length L (Metric)

35.0

Fixation Method

Fir Tree

Width W (Imperial)

0.47

Width W (Metric)

12.0

Bundle Diameter Min (Imperial)

0.39

Bundle Diameter Min (Metric)

10.0

Bundle Diameter Max (Imperial)

0.55

Bundle Diameter Max (Metric)

14.0

Cable Ties T50R

Height H (Imperial) 2.30

Height H (Metric) 58.75

Panel Thickness Min(Imperial) 0.02

Panel Thickness Max(Imperial) 0.27

Panel Thickness Min (Metric) 0.60

Panel Thickness Max (Metric) 6.75

Mounting Hole Diameter D (Imperial) 0.35 x 0.47 " 0.35 x 0.55

Mounting Hole Diameter D (Metric) 9.0 x 14.0 mm 9.0 x 12.0 mm

Mounting Hole Diameter D Min (Imperial) 0.35

Mounting Hole Diameter D Max (Imperial) 0.55

Mounting Hole Diameter D Max (Metric) 14.0

Disc Diameter(Metric) 23.63

Disc Diameter (Imperial) 0.93

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability

UL 94 HB

Operating Temperature (Metric)

-40°F to +230°F (-40°C to +110°C)

ROHS Complaint

Yes

Package Quantity(Imperial)

500

Package Quantity (Metric)

500