

## Specification Sheet

Part Number: 151-02569



Integrated design allows for easy insertion by hand

0.75–1.25 mm panel thickness range allows for multiple applications

Double-compression design that accommodates various sizes of wire and cable

Presents a high extraction force for withstanding extreme conditions

Low Profile 90° Metal Edge Clip, 0.76–1.24mm Panel Thickness, 4–7.4mm Cable Range, SS304, 100/box

**Article Number** 151-02569

**Type** MSC901

**Color** Metal (ML)

**Quantity Per** bag

**Product Description** HellermannTyton's Metal Edge Clip provides an excellent alternative to managing wire and PV cables where plastic fasteners are not the preferred method. Designed for effortless insertion, the Metal Edge Clip has a high extraction force that tolerates extreme environments and provides assurance that the cables are secure on a panel. The Metal Edge Clip is simple to install and can easily be removed with a flathead screwdriver.

**Short Description** Low Profile 90° Metal Edge Clip, 0.76–1.24mm Panel Thickness, 4–7.4mm Cable Range, SS304, 100/box

<b>Global Part Name</b>	MSC901-SS304-SR
<b>Length L (Imperial)</b>	0.73
<b>Length L (Metric)</b>	18.44
<b>Width W (Imperial)</b>	0.460
<b>Width W (Metric)</b>	11.57
<b>Panel Thickness Min (Imperial)</b>	0.03
<b>Panel Thickness Max (Imperial)</b>	0.049
<b>Panel Thickness Min (Metric)</b>	0.76
<b>Panel Thickness Max (Metric)</b>	1.24
<b>Material</b>	Stainless Steel (SS304)
<b>Material Shortcut</b>	SS304
<b>Flammability</b>	Non-Burning
<b>Halogen Free</b>	No
<b>Operating Temperature</b>	-112°F to +1000°F (-80°C to +538°C)

**Reach Compliant (Article 33)** Yes

**ROHS Compliant** Yes

**UL Recognized (US)** Yes

**UL Listed (US and Canada)** Yes

**UL Recognized (US and Canada)** Yes

**UL Listed (US)** Yes

**Package Quantity (Imperial)** 100 pieces

**Package Quantity (Metric)** 100