

Specification Sheet

Part Number: 151-02609



Can be easily assembled to convoluted tubing and reliably remain in position Internal rib prevents movement or rattling Multiple configurations to mount to a variety of surfaces Releaseable to allow for maintenance

Conduit Clamps, Size 25, Mounting Hole 10.6 mm, Offset 60.15 mm, PA66HIRHS, Black, 500/pkg

Article Number	151-02609
Type	CDC25S60.5M10
Color	Black (BK)
Quantity Per	carton
Product Description	The Convoluted Tubing Clamp provides a quick method for securing and routing convoluted tubing. The clamp has an internal rib that prevents movement of the tubing and rattling. Living hinge allows placement and positioning of tubing before locking in place. Convoluted tubing clamps are available in various tubing diameters.
Short Description	Conduit Clamps, Size 25, Mounting Hole 10.6 mm, Offset 60.15 mm, PA66HIRHS, Black, 500/pkg

Global Part Name CDC25S60.5M10-PA66HIRHS-BK

Length L (Imperial) 3.73

Length L (Metric) 94.7

Offset Length (Imperial) 2.38

Offset Length (Metric) 60.5

Fixation Method screwable

Width W (Imperial) 0.9

Width W (Metric) 23

Bundle Diameter Max (Imperial) 0.98

Bundle Diameter Max (Metric) 25.0

Height H (Imperial) 3.13

Height H (Metric) 79.6

Diameter D (Imperial) 1.06

Diameter D (Metric) 27.0

Mounting Hole Diameter D (Imperial) 0.42

Mounting Hole Diameter D (Metric) 10.6 mm

Stud Diameter (Metric)	M10
Stud Diameter (Imperial)	M10
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL 94 HB
Halogen Free	No
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500