

Specification Sheet

Part Number: 151-02611



Can be easily assembled to convoluted tubing and reliably remain in position.

Internal rib prevents movement or rattling.

Multiple configurations to mount to a variety of surfaces.

Releaseable to allow for maintenance.

Conduit Clamps, Size 19, Mounting Hole 10.6 mm, Offset 40.5 mm, PA66HIRHS, Black, 800/pkg

Article Number 151-02611

Type CDC19S40.5M10

Color Black (BK)

Quantity Per carton

Product Description The Convoluted Tubing Clamp provides a quick method for securing and routing convoluted tubing. The clamp has an internal rib that prevents movement of the tubing and rattling. Living hinge allows placement and positioning of tubing before locking in place. Convoluted tubing clamps are available in various tubing diameters.

Short Description Conduit Clamps, Size 19, Mounting Hole 10.6 mm, Offset 40.5 mm, PA66HIRHS, Black, 800/pkg

Global Part Name CDC19S40.5M10-PA66HIRHS-BK

Length L (Imperial) 2.77

Length L (Metric) 70.3

Offset Length (Imperial) 1.59

Offset Length (Metric) 40.5

Fixation Method screwable

Width W (Imperial) 0.9

Width W (Metric) 23

Bundle Diameter Max (Imperial) 0.75

Bundle Diameter Max (Metric) 19.0

Height H (Imperial) 2.63

Height H (Metric) 66.8

Diameter D (Imperial) 0.81

Diameter D (Metric) 20.6

Mounting Hole Diameter D (Imperial) 0.42

Mounting Hole Diameter D (Metric) 10.6 mm

Stud Diameter (Metric)	M10
Stud Diameter (Imperial)	M10
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL 94 HB
Halogen Free	No
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	800
Package Quantity (Metric)	800