

## Specification Sheet

Part Number: 151-02617



Can be easily assembled to convoluted tubing and reliably remain in position

Internal rib prevents movement or rattling

Multiple configurations to mount to a variety of surfaces

Releaseable to allow for maintenance

Conduit Clamps, Size 13, Mounting Hole 6.5 mm, Offset 20.2 mm, PA66, Black, 500/carton

**Article Number** 151-02617

**Type** CDC13OSL20.15M10

**Color** Black (BK)

**Quantity Per** carton

**Product Description** The Convoluted Tubing Clamp provides a quick method for securing and routing convoluted tubing. The clamp has an internal rib that prevents movement of the tubing and rattling. Living hinge allows placement and positioning of tubing before locking in place. Convoluted tubing clamps are available in various tubing diameters.

**Short Description** Conduit Clamps, Size 13, Mounting Hole 6.5 mm, Offset 20.2 mm, PA66, Black, 500/carton

**Global Part Name** CDC13OSL20.15M10-PA66-BK

**Length L (Imperial)** 1.9

**Length L (Metric)** 48.2

**Offset Length (Imperial)** 0.8

**Offset Length (Metric)** 20.2

**Fixation Method** screwable

**Width W (Imperial)** 1.8

**Width W (Metric)** 45

**Bundle Diameter Max (Imperial)** 0.51

**Bundle Diameter Max (Metric)** 13.0

**Height H (Imperial)** 2.07

**Height H (Metric)** 52.8

**Diameter D (Imperial)** 0.55

**Diameter D (Metric)** 14.0

**Mounting Hole Diameter D (Imperial)** 0.26

**Mounting Hole Diameter D (Metric)** 6.5 mm

<b>Stud Diameter (Metric)</b>	M10
<b>Stud Diameter (Imperial)</b>	M10
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V-2
<b>Halogen Free</b>	No
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500