

Specification Sheet

Part Number: 151-02619



Can be easily assembled to convoluted tubing and reliably remain in position

Internal rib prevents movement or rattling

Multiple configurations to mount to a variety of surfaces

Releaseable to allow for maintenance

Conduit Clamps, Size 22, Mounting Hole 10.6 mm, Offset 60.5 mm, PA66, Black, 600/carton

Article Number 151-02619

Type CDC22OSR60.5M10

Color Black (BK)

Quantity Per carton

Product Description The Convoluted Tubing Clamp provides a quick method for securing and routing convoluted tubing. The clamp has an internal rib that prevents movement of the tubing and rattling. Living hinge allows placement and positioning of tubing before locking in place. Convoluted tubing clamps are available in various tubing diameters.

Short Description Conduit Clamps, Size 22, Mounting Hole 10.6 mm, Offset 60.5 mm, PA66, Black, 600/carton

Global Part Name CDC22OSR60.5M10-PA66-BK

Length L (Imperial) 3.65

Length L (Metric) 92.7

Offset Length (Imperial) 2.38

Offset Length (Metric) 60.5

Fixation Method screwable

Width W (Imperial) 0.9

Width W (Metric) 23

Bundle Diameter Max (Imperial) 0.87

Bundle Diameter Max (Metric) 22.0

Height H (Imperial) 2.87

Height H (Metric) 72.8

Diameter D (Imperial) 0.93

Diameter D (Metric) 23.7

Mounting Hole Diameter D (Imperial) 0.42

Mounting Hole Diameter D (Metric) 10.6 mm

Stud Diameter (Metric)	M10
Stud Diameter (Imperial)	M10
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V-2
Halogen Free	No
UV Resistant (Yes/No)	No
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	600
Package Quantity (Metric)	600

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach

to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)