

Specification Sheet

Part Number: 151-02643



Can be easily assembled to convoluted tubing and reliably remain in position Internal rib prevents movement or rattling Multiple configurations to mount to a variety of surfaces Releaseable to allow for maintenance

Conduit Clamps, Size 6, Mounting Hole 6.5 mm, Offset 50.0 mm, PP, Black, 500/pkg

Article Number 151-02643

Type CDC6B90OS50.5M6

Color Black (BK)

Quantity Per carton

Product Description The Convoluted Tubing Clamp provides a quick method for securing and routing convoluted tubing. The clamp has an internal rib that prevents movement of the tubing and rattling. Living hinge allows placement and positioning of tubing before locking in place. Convoluted tubing clamps are available in various tubing diameters.

Short Description Conduit Clamps, Size 6, Mounting Hole 6.5 mm, Offset 50.0 mm, PP, Black, 500/pkg

Global Part Name CDC6B90OS50.5M6-PP-BK

Length L (Imperial) 2.5

Length L (Metric) 63.5

Offset Length (Imperial) 1.97

Offset Length (Metric) 50.0

Fixation Method screwable

Width W (Imperial) 0.9

Width W (Metric) 23

Bundle Diameter Max (Imperial) 0.24

Bundle Diameter Max (Metric) 6.0

Height H (Imperial) 2.22

Height H (Metric) 56.3

Diameter D (Imperial) 0.31

Diameter D (Metric) 8.0

Mounting Hole Diameter D (Imperial) 0.26

Mounting Hole Diameter D (Metric) 6.5 mm

Stud Diameter (Metric)	M6
Stud Diameter (Imperial)	M6
Material	Polypropylene (PP)
Material Shortcut	PP
Flammability	UL 94 HB
Halogen Free	No
Operating Temperature	-40°F to +239°F (-40°C to +115°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500