

Specification Sheet

Part Number: 151-02686



Can be easily assembled to convoluted tubing and reliably remain in position

Internal rib prevents movement or rattling

Multiple configurations to mount to a variety of surfaces

Releaseable to allow for maintenance

Conduit Clamps, Size 10 and 13, Mounting Hole 6.35 mm, Threaded, PP, Black, 1600/pkg

Article Number 151-02686

Type CDC10-13AM6

Color Black (BK)

Quantity Per carton

Product Description The Convoluted Tubing Clamp provides a quick method for securing and routing convoluted tubing. The clamp has an internal rib that prevents movement of the tubing and rattling. Living hinge allows placement and positioning of tubing before locking in place. Convoluted tubing clamps are available in various tubing diameters.

Short Description Conduit Clamps, Size 10 and 13, Mounting Hole 6.35 mm, Threaded, PP, Black, 1600/pkg

Global Part Name CDC10-13AM6-PP-BK

Length L (Imperial) 2.6

Length L (Metric) 66.0

Offset Length (Imperial) 0.86

Offset Length (Metric) 21.8

Fixation Method screwable

Variant Threaded

Width W (Imperial) 0.5

Width W (Metric) 12.7

Bundle Diameter Max (Imperial) 0.51

Bundle Diameter Max (Metric) 13.0

Height H (Imperial) 0.57

Height H (Metric) 14.5

Diameter D (Imperial) 0.54

Diameter D (Metric) 13.6

Mounting Hole Diameter D (Imperial) 0.25

Mounting Hole Diameter D (Metric) 6.35 mm

Stud Diameter (Metric) M6

Stud Diameter (Imperial) M6

Material Polypropylene (PP)

Material Shortcut PP

Flammability UL 94 HB

Halogen Free No

Operating Temperature -40°F to +239°F (-40°C to +115°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 1600

Package Quantity (Metric) 1600

