

Specification Sheet

Part Number: 151-02693

Can be easily assembled to convoluted tubing and reliably remain in position

Internal rib prevents movement or rattling

Multiple configurations to mount to a variety of surfaces

Releaseable to allow for maintenance



Conduit Clamps, Size 25, Mounting Hole 6.35 mm, Arrowhead, PP, Gray, 1700/Pkg

Article Number 151-02693

Type CDC25AH6.35

Color Gray (GY)

Quantity Per carton

Product Description The Convoluted Tubing Clamp provides a quick method for securing and routing convoluted tubing. The clamp has an internal rib that prevents movement of the tubing and rattling. Convoluted tubing clamps are available in various tubing diameters. Choose from arrowhead, fir tree, bundling clip, bracket and dual clamp configurations.

Short Description Conduit Clamps, Size 25, Mounting Hole 6.35 mm, Arrowhead, PP, Gray, 1700/Pkg

Global Part Name CDC25AH6.35-PP-GY

Length L (Imperial) 2.52

Length L (Metric) 64.0

Fixation Method Arrowhead

Width W (Imperial) 0.4

Width W (Metric) 10.2

Bundle Diameter Max (Imperial) 0.98

Bundle Diameter Max (Metric) 25.0

Height H (Imperial) 3.2

Height H (Metric) 81.2

Diameter D (Imperial) 1.06

Diameter D (Metric) 27.0

Mounting Hole Diameter D (Imperial) 0.25

Mounting Hole Diameter D (Metric) 6.35 mm

Material Polypropylene (PP)

| | |
|------------------------------|-----------------------------------|
| Material Shortcut | PP |
| Flammability | UL 94 HB |
| Halogen Free | No |
| UV Resistant (Yes/No) | No |
| Operating Temperature | -40°F to +239°F (-40°C to +115°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 1700 |
| Package Quantity (Metric) | 1700 |

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)