

Specification Sheet

Part Number: 151-02710



Can be easily assembled to convoluted tubing and reliably remain in position

Internal rib prevents movement or rattling

Multiple configurations to mount to a variety of surfaces

Releaseable to allow for maintenance

Conduit Clamps, Size 16, Mounting Hole 6.68, Fir Tree, PP, Black, 1000/Pkg

Article Number 151-02710

Type CDC16B90FT6.68

Color Black (BK)

Quantity Per carton

Product Description The Convoluted Tubing Clamp provides a quick method for securing and routing convoluted tubing. The clamp has an internal rib that prevents movement of the tubing and rattling. Convoluted tubing clamps are available in various tubing diameters. Choose from arrowhead, fir tree, bundling clip, bracket and dual clamp configurations.

Short Description Conduit Clamps, Size 16, Mounting Hole 6.68, Fir Tree, PP, Black, 1000/Pkg

Global Part Name CDC16B90FT6.68-PP-BK

Length L (Imperial) 2.48

Length L (Metric) 62.9

Offset Length (Imperial) 1.5

Offset Length (Metric) 38.0

Fixation Method Fir Tree

Width W (Imperial) 0.3

Width W (Metric) 7.6

Bundle Diameter Max (Imperial) 0.63

Bundle Diameter Max (Metric) 16.0

Height H (Imperial) 2.67

Height H (Metric) 67.8

Diameter D (Imperial) 0.69

Diameter D (Metric) 17.4

Mounting Hole Diameter D (Imperial) 0.26

Mounting Hole Diameter D (Metric) 6.68 mm

Material	Polypropylene (PP)
Material Shortcut	PP
Flammability	UL 94 HB
Halogen Free	No
UV Resistant (Yes/No)	No
Operating Temperature	-40°F to +239°F (-40°C to +115°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

