

Specification Sheet

Part Number: 151-02727



Can be easily assembled to convoluted tubing and reliably remain in position

Internal rib prevents movement or rattling

Multiple configurations to mount to a variety of surfaces

Releaseable to allow for maintenance

Conduit Clamps, Size 16, Mounting Hole 6.54, Arrowhead, PA66HIRHS, Black, 900/Pkg

Article Number 151-02727

Type CDC16AHW6.54

Color Black (BK)

Quantity Per carton

Product Description The Convoluted Tubing Clamp provides a quick method for securing and routing convoluted tubing. The clamp has an internal rib that prevents movement of the tubing and rattling. Convoluted tubing clamps are available in various tubing diameters. Choose from arrowhead, fir tree, bundling clip, bracket and dual clamp configurations.

Short Description Conduit Clamps, Size 16, Mounting Hole 6.54, Arrowhead, PA66HIRHS, Black, 900/Pkg

| | |
|-------------------------------------|--|
| Global Part Name | CDC16AHW6.54-PA66HIRHS-BK |
| Length L (Imperial) | 2.11 |
| Length L (Metric) | 53.7 |
| Fixation Method | Arrowhead |
| Width W (Imperial) | 0.4 |
| Width W (Metric) | 10.2 |
| Bundle Diameter Max (Imperial) | 0.63 |
| Bundle Diameter Max (Metric) | 16.0 |
| Height H (Imperial) | 2.76 |
| Height H (Metric) | 70.1 |
| Diameter D (Imperial) | 0.69 |
| Diameter D (Metric) | 17.4 |
| Mounting Hole Diameter D (Imperial) | 0.26 |
| Mounting Hole Diameter D (Metric) | 6.54 mm |
| Material | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |

| | |
|------------------------------|-----------------------------------|
| Material Shortcut | PA66HIRHS |
| Flammability | UL 94 HB |
| Halogen Free | No |
| UV Resistant (Yes/No) | No |
| Operating Temperature | -40°F to +230°F (-40°C to +110°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 900 |
| Package Quantity (Metric) | 900 |

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)